

SAFETY DATA SHEET

1. Identification

Product Name: C-20

Synonyms: N/A

Product Use: Reverse Osmosis Membrane Cleaner

Manufacturer/Supplier: AXEON Water Technologies

Address: 40980 County Center Drive #100,
Temecula, California, 92591, USA

Fileder Filter Systems Ltd

St. Leonard's Road, 20/20 Maidstone
Kent, ME16 0LS, UK

Tel: 0044 (0)1622 691886

Emergency Tel: 0044 (0)7970 633392

General Information: 800-320-4074

Transportation Emergency Number:

CHEMTREC: 800-424-9300 (Domestic North America) OR 703-527-3887 (International, collect calls accepted)

2. Hazard Identification

Classification:

Health	Environmental	Physical
Acute Toxicity – Oral Category 4 Skin Corrosive – Category 1B Eye Corrosive – Category 1 STOT-SE – Category 3	Acute Aquatic – Category 3	Corrosive to Metals – Category 1 Oxidizing Solid – Category 3

Pictograms:



Hazard Statements

DANGER

Causes serious eye damage
Cause severe skin burns and eye damage
May cause respiratory irritation; or
May cause drowsiness or dizziness
May be corrosive to metals
Harmful if swallowed
May intensify fire; oxidizer

Precautionary Statements

Wear protective gloves, clothing and eye/face protection. Do not breathe dust, spray, or mist.
If on skin (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If inhaled: Remove person to fresh air and keep comfortable for breathing
If swallowed or inhaled: Call poison center or physician if you feel unwell.
Wash exposed areas thoroughly after handling.

Do not eat, drink or smoke when using this product. Specific treatment see Section 4 (First aid measures).

Store container tightly closed in cool/well-ventilated place. Immediately call a poison center or physician.

Wash contaminated clothing before reuse. Store locked up.

Keep away from heat.

Keep/Store away from clothing and other combustible materials. Take any precaution to avoid mixing with combustibles.

In case of fire: Use media appropriate for primary cause of fire. Absorb spillage to prevent material damage.

Keep only in original container.

Store in a corrosive resistant HDPE/PE/PP container with a resistant inner liner.

Only use outdoors or in a well-ventilated area.

Dispose of contents/container in accordance with local/state/federal regulations.

3. Composition / Information on Ingredients

The specific chemical identities and exact percentages of composition have been withheld as a trade secret.

4. First Aid Measures

Eye: Eye irritation. Flush immediately with large amounts of water for at least 30 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Get immediate medical attention.

Skin: Itching or irritation of the skin. Immediately flush the skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Do not remove clothing if it sticks to skin. Use alkaline soap if available. Wash contaminated clothing before reuse.

Inhalation: For nasal irritation, remove exposed person from source of exposure to fresh air. If not breathing, clear airway and start cardiopulmonary resuscitation (CPR). Get immediate medical attention.

Ingestion: Do NOT induce vomiting. Give large quantities of milk and water. Never give anything by mouth to an unconscious person. Call a physician immediately.

5. Fire Fighting Measures

Suitable Extinguishing Media: Use media appropriate to primary cause of fire. Use water to cool fire-exposed containers, structures and to protect personnel. Use water to dilute spills and to flush them away from sources of ignition.

Fire Fighting Procedures: Use water spray to cool containers exposed to fire. Minimize exposure. Do not breathe fumes. Contain run-off. A respirator that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements should be worn if conditions warrant the use of a respirator.

Unusual Fire and Explosion Hazards: Product is an oxidizer; keep away from heat and/or combustible materials.

Combustion Products: Will emit toxic gases and form corrosive vapors and potassium/nitrogen oxides upon thermal decomposition.

6. Accidental Release Measures

Personal Protective Equipment: Protective clothing including chemical splash goggles, Latex, nitrile, or butyl rubber full-length gloves, rubber apron made of nitrile or butyl rubber, and rubber overshoes must be worn during spill clean-ups and deactivation of material. If this material comes into contact with the skin during clean-up operations, immediately remove all contaminated clothing and wash exposed skin with soap and water. See section 4, First Aid Measures, for further information.

Land Spill: Wearing recommended protective clothing and equipment, dike spill with soil, sand, or compatible commercial absorbent. Remove remaining liquid with a pump, vacuum truck, or absorb liquid in sand or commercial absorbent. Place waste in approved containers for disposal. Dispose waste according to Federal, State, and local regulations.

Water Spill: Wear protective clothing and equipment. Stop flow. Dike contaminated water and remove for disposal and/or treatment. Notify proper authorities and all downstream users if possible. Dispose of Solid Waste according to Federal, State, and Local Regulations.

7. Handling and Storage

Handling: Do not get in eyes, on skin or on clothing. Do not breathe dust or mists. Keep container closed. Use only with adequate ventilation. Use good hygiene practices. Wash hands before eating, drinking or smoking. Remove contaminated clothing and clean before re-use.

Storage Conditions: Store in tightly closed containers in cool, dry, well-ventilated area away from incompatibles. The maximum storage temperature for this material is 55°C/131°F. The minimum storage temperature for this material is 0°C/32°F. Do not store this material in containers made of steel.

8. Exposure Controls / Personal Protection

Exposure limits

Component	OSHA PEL (TWA)	Cal-OSHA (8-hour, TWA, ceiling)	ACGIH TVL (ceiling)
Sodium Hydroxide	2 mg/m ³	2 mg/m ³	2 mg/m ³

Engineering Controls: Use local exhaust ventilation at the point of dust or mist evolution. Have safety shower and eye wash station available where exposure can occur.

Personal Protective Equipment (PPE)

Respiratory Protection: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator use. Use air purifying respirators within use limitations associated with the equipment or else use supplied air-respirators. If air-purifying respirator use is appropriate, use a respirator with organic/acid gas cartridge and dust/mist prefilters. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air supplied respirator. Warning air purifying respirators do not protect workers in oxygen deficient atmospheres.

Eye Protection: Splash goggles and/or face shield (ANSI Z87.1 or approved equivalent).

Skin Protection: Wear impervious protective clothing. Use butyl (or Teflon for limited contact) gloves, boots, and coveralls. Remove gloves after use. Wash hands with soap and water.

9. Physical and Chemical Properties

Appearance: White powder

Odor: None

Density: Approximately 9 lbs./gallon

Specific Gravity: N/A

Percentage Volatile: 1% Water – Max

Evaporation Rate: N/A

pH of Solution: 10.5 – 12

Water Solubility: Complete

Boiling Point: N/A

Melting/Freezing Point: N/A

Vapor Pressure: N/A

Vapor Density: Same as air

Auto-ignition Temperature: N/A

Flash point: N/A

Flammability: N/A

Flammable Limits:

LEL (Lower Explosive Limits): N/A

UEL (Upper Explosive Limits): N/A

10. Stability and Reactivity

Stability/Incompatibility: Incompatible with strong acids. Stable under normal storage conditions; see Section 7 (Handling and Storage) for specific conditions.

Hazardous Reactions/Decomposition Products: Will emit toxic gases and form corrosive vapors and potassium/nitrogen oxides upon thermal decomposition.

11. Toxicological Information

Acute Toxicity Information

C-20:

Oral (LD50) Rat – 1,854 mg/kg
Dermal (LD50) Rabbit – 3,468 mg/kg

Signs and Symptoms of Overexposure: Eye and nasal irritation, headache, dizziness, nausea, vomiting, difficulty breathing, weakness, itching or burning of the skin.

Acute Affects: Harmful if swallowed.

Eye Contact: Will cause serious or permanent eye damage.

Skin Contact: Will cause severe burns and/or reddening.

Inhalation: May cause severe respiratory irritation.

Ingestion: May cause burns to the gastric/intestinal mucosa.

Chronic Effects: None known

Medical Conditions Aggravated by Exposure: Conditions of the lungs may be aggravated by exposure.

12. Ecological Information

EC50 (Daphnia magna) = 8 mg/L / 48hr

EC50 (Danio Rerio) = 25 mg/L / 96hr

Bioaccumulation potential is low, as the product is considered biodegradable.

13. Disposal Considerations:

Dispose of in accordance with Federal, State, and Local regulations and permits. Refer to state and local requirements for any additional requirements, as these may be different from Federal laws and regulations. Chemical additions, processing, or otherwise altering this material may make management information presented in the SDS incomplete, inaccurate or otherwise inappropriate.

14. Transportation Information

U.S. Department of Transportation (DOT)

Proper Shipping Name: Oxidizing Solid, Corrosive, N.O.S. (Sodium Perborate, Sodium Hydroxide)

Hazard Class: 5.1, 8

Hazardous Ingredients: Sodium Perborate, Sodium Hydroxide

UN/NA Number: 3085

Packing Group: II

Labels Required: Corrosive, Oxidizing

International Maritime Organization (IMDG)

Proper Shipping Name: Oxidizing Solid, Corrosive, N.O.S. (Sodium Perborate, Sodium Hydroxide)

Hazard Class: 5.1, 8

Hazardous Ingredients: Sodium Perborate, Sodium Hydroxide

UN/NA Number: 3085 Packing Group: II

Labels Required: Corrosive, Oxidizing

15. Regulatory Information

U.S. Federal Regulations

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA):

C-20 has a reportable quantity of 1,000 (lbs). If appropriate, immediately report to the National Response Center (800/424-8802) as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies.

Toxic Substances Control Act (TSCA): All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substance Control Act (TSCA) Chemical Substance Inventory.

Clean Water Act (CWA): C-20 is not a hazardous substance under the Clean Water Act. Consult Federal, State and local regulations for specific requirements.

Clean Air Act (CAA): C-20 is not a hazardous substance under the Clean Air Act. Consult Federal, State and local regulations for specific requirements.

Superfund Amendments and Reauthorization Act (SARA) Title III Information:

SARA Section 313 Notification (40CFR 372)

None of the components are subject to the reporting levels established by SARA Title III, Section 313.

State Regulations

California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Pennsylvania Right To Know Components:

Sodium peroxometaborate monohydrate – CAS # 10332-33-9

Tetrapotassium pyrophosphate – CAS # 7320-34-5

New Jersey Right To Know Components:

Sodium peroxometaborate monohydrate – CAS # 10332-33-9

Tetrapotassium pyrophosphate – CAS # 7320-34-5

International Regulations

Canadian Environmental Protection Act: All of the components of this product are included on the Canadian Domestic Substances list (DSL).

Canadian Workplace Hazardous Materials Information System (WHMIS):

E=Corrosive



This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

European Inventory of Existing Chemicals (EINECS): All of the components of this product are included on EINECS.

EU Classification:

EU Risk (R) and Safety (S) Phrases:

R34: Causes burns.

R36/37/38: Irritating to eyes, respiratory system and skin. R41:

Risk of serious damage to eyes.

R65: Harmful - may cause lung damage if swallowed.

S9: Keep container in a well-ventilated place.

S24/25: Avoid contact with skin and eyes.

S27/28: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (Section 4)

S53: Avoid exposure - obtain special instructions before use.

S57: Use appropriate container to avoid environmental contamination.

16. Other Information

Revision Date: October 21, 2015

Disclaimer: This SDS is provided as an information resource only. This document should not be taken as a warranty for which AXEON Water Technologies assumes legal responsibility. The information contained within this SDS was provided by raw materials and other reliable sources. The buyer assumes all responsibility of using and handling the product in accordance with applicable federal, state, and local regulations.