

TECHNICAL SHEET

STANDARD HOUSINGS
FILTER HOUSINGS



TECHNICAL SHEET



PENTAIR STANDARD HOUSINGS

TECHNICAL CHARACTERISTICS

- Types of cartridges: Ø: 2 1/2" to 2 7/8"
- Option: pressure relief
- Maximum temperature: 51.7°C
- Maximum pressure: 8.62 bar
- Housing: polypropylene (opaque) or styrene acrylonitrile (clear)
- Cap: reinforced polypropylene
- Button assembly: 300-series stainless steel, EPDM and polypropylene
- O-ring: Buna-N



PERFORMANCE CHARACTERISTICS

Model	Initial ΔP @ flow rate
#10 Opaque	0.07 bar @ 38 Lpm
#10 Clear	0.07 bar @ 38 Lpm
#20 Opaque	0.07 bar @ 38 Lpm

PRODUCT SPECIFICATIONS

Model	Maximum dimensions	Inlet/outlet ports
#10 Opaque	311 x 130 mm (12 1/4" x 5 1/8")	3/4" BSP or NPT
#10 Clear	321 x 133 mm (12 5/8" x 5 1/4")	3/4" BSP or NPT
#20 Opaque	568 x 130 mm (22 3/8" x 5 1/8")	3/4" BSP or NPT

WARNING

Protect against freezing to prevent cracking of the filter and water leakage



Housings are tested and certified by NSF International to NSF/ANSI Standard 42 for material and structural integrity requirements.

www.pentairaquaeurope.com